Characterisation and optimisation of ladle stirring systems for The steelmaking industry

DISSTECH WORK SHOP

Kista 2017-05-23


jonas alexis@swerea.se


Jonas Alexis





# Control of inclusions in RH degassing processes

#### Velocity Vector Field [m/s]









CO Content in gaseous phases

Carbon content in the melt [ppm]



## Control of inclusion, slag foaming and temperature in vacuum degassing


Open eye size vs. Slag viscosity and flow rate:

Case	Flow rate [I/min]	Slag Thickness [cm]	Slag viscosity [Pa.s]			
1	80	10	4.3e-4			
2	80	25	4.3e-4		sking tilskingsoming can sking viscoming-alleidette Fact (p. et ill bleds	 What Shinksman III can they obscuring #0.86649 Prote C = 60 Pages
3	80	10	8.0e-3			- 6
4	120	10	8.0e-3			
$k_r^N = \frac{0.015 \cdot f^2_N}{1.0161}$			Action and the con-			
,	1+	$161 \cdot a_o +$	+ 63.4 · a	$a_{S}$	clas chick com 10 cm dag viscosom 0.000 Pate () = 40 toma	 Ang thickness—IV to Fag viscosity-tilest hads On 128 trains

PART OF RISE

# Production of EAF steels with low content of N2 and S through vacuum treatment


Concentration profile of nitrogen




### Improvment of inclusion floatation during RH treatment

Geometry and its schematic:






Open eye for ecentric plug







Effects of viscosity on the size of the open eye:




Q=200 l/min, v (slag) = 4.6e-5 m2s-1




Q=200 l/min, v (slag) = 4.6e-4 m2s-1




Q=200 l/min, 
$$v$$
 (slag) = 4.6e-3 m2s-1



Q=200 l/min, v (slag) = 4.6e-2 m2s-1



Q=200 l/min, v (slag) = 4.6e-1 m2s-1



Q=50 l/min, 
$$v$$
 (slag) = 4.6e-1 m2s-1

PART OF RI.SE



Water model:






Q=3.6 l/min


Q=9.2 l/min

Q=25.2 l/min

oil height: 2 cm, centric plug



Q=3.6 l/min




Q=7.0 l/min




Q=20.2 l/min

swerea

Open eye size vs. Oil height




H = 20 mm




H = 40 mm

gas flow: 3.6 l/min, centric plug

Open eye vs. Plug position and number








Centric Eccentric Double lance


CFD vs. Water model







### Improved control of inclusion chemistry and steel cleanness in the ladle furnace

Slag-metal interface modelling:








### Improved control of inclusion chemistry and steel cleanness in the ladle furnace

Flow profile for different variants:

Case	Plug 1 [l/min]	Plug 2 [l/min]
1	60	60
2	120	120
3	200	200
4	60	200


# Case 3


#### Improved control of inclusion chemistry and steel cleanness in the ladle furnace



#### Improved control of inclusion chemistry and steel cleanness in the ladle furnace

Inclusions separation:






Variant 3



## Resource-saving operation of stainless steel refining in VOD and AOD processes

 Distribution of carbon concentrations in % for an AOD heat at start of inert gas blowing, after 10s and after 30s.







#### **Summary**

- RH degasser:
  - Melt conposition
  - Inclusion model
  - Temperature profile and heat transfer
- Ladle:
  - Stirring: gas and/or industion
  - Arc heating
  - Homogenization
  - Melt composition
  - Inclusion model
- AOD and VOD:
  - Melt composition
  - Temperature profile
  - Decarburization
- The newest simulation work is at least 6 years old!





#### Why stirring?

- Improves the kinetics so that equilibrium conditions are met faster
- Homogenization with respect to dissolved elements as well as temperature
- Promote the separation of inclusions to slag





#### Porous plugs


Slot plug

Segment plug

Hybrid plug









#### Bubble columns


Slot plug



Hybrid plug









swerea swedish research

#### Homogenization Times




Medel=85 s Std.av=14 s Medel=99 s Std.av=16 s Medel=102 s Std.av=19 s








### Symmetric gas flow







PART OF RI.SE




### Asymmetric gas flow



#### Effect on flow




Homogenization time






### Number of plugs






### Refining times



PART OF RI.S




### Ladle age






#### Electromagnetic stirring forces



PART OF RI.SE




### Open eye size








#### Geometries






### Refining operations




### Ladle geometry










### Plug placement





### Gas plumes










#### Industrial ladles



PART OF **RI**.





Scientific Work for Industrial Use www.swerea.se